


ITEM	Hoshizaki Reach-in Refrigerator
MODEL	HRE-188SC-P
POWER SUPPLY	1 Phase 230V~ 60Hz Capacity: 0.70kVA (3.20A)
AMPERAGE	Rated: 3.0A Starting: 7.00A
ELECTRIC CONSUMPTION	MOTOR 256W(POWER FACTOR 54%) Heater 435W Refrigeration 441W Defrost 250W
HEAT REJECTION	986W
POWER CORD	2.0m (Plug with Earth Wire)
EFFECTIVE CAPACITY	1715L
OUTSIDE DIMENSIONS	1800mm(W)×800mm(D)×2050(−2080)mm(H)
INSIDE DIMENSIONS	1696mm(W)×646mm(D)×1484mm(H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear / Bottom), PP (Handle on Door)
INTERIOR	Stainless Steel, ABS Plastic
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Heater
COMPRESSOR	Hermetic, Inverter
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube type
REFRIGERANT	R290 / 110g
TEMPERATURE CONTROL	Microprocesso controlled Adjustable from −6 to 12° C
DEFROST CONTROL	Microprocessor
ELECTRIC CIRCUIT PROTECTION	Earth Wire, Circuit Breaker
COMPRESSOR PROTECTION	Inverter Protector (Auto-reset)
LEG	Plastic Adjustable from 150 to 180mm
SHELF	12 pcs.
WEIGHT	Net: 191kg (Gross:Approx. 226kg)
PACKAGE	Carton (Wooden Pallet) 1860mm(W)×920mm(D)×2075mm(H)
ACCESSORIES	Drain Hose×1, Drain Pan ×1
OPERATING CONDITIONS	Ambient Temperature: 5–43°C Voltage Range: Rated Voltage±6%

[illegible]

HOSHIZAKI REACH-IN REFRIGERATOR HRE-188SC-P

APPROVED LIANGK	CHECKED LIUH	DESIGNED LIUH	DRAWN LXF	SCALE 1/20	TRIGONOMETRY		
**	**		****	DATE 2025.11.13	DRAWING NO. D43967	SYMBOL 	
APPROVED	DESIGNED	SYMBOL	DATE				