



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001



Compliant with
IEC60335-2-89 Standard

HR-128MC-SLD

UPRIGHT LONG SOLID DOOR REFRIGERATOR




Key Features



Lower running cost



Powerful cooling
performance




Self Closing Door



Removal door gaskets



Food Guard Shelf



Round Interior Corners



Large and clear display




Drainage-Free Design



LED lighting



Dimensions & Specifications



MODEL	HR-128MC-SLD
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.63kVA (2.90A)
ELECTRIC CONSUMPTION	319W
TEMPERATURE CONTROL	-6 to 12°C
STORAGE CAPACITY	1043L
WEIGHT	Net: 132kg (Gross: Approx. 161kg)
OUTSIDE DIMENSIONS	1200mm(W)× 800mm(D)×2050(-2080)mm(H)
PACKAGE	Carton(Wooden Pallet): 1260mm(W)×900mm(D)×2075mm(H)
NUMBER OF SHELVES	8pcs
REFRIGERANT	R290
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI SINGAPORE PTE. LTD.

18 Boon Lay Way #01-102 Tradehub21, 609966

TEL 6225 2612 FAX 6225 3219

www.hoshizaki.com.sg

