



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001



Compliant with
IEC60335-2-89 Standard

HR-148MC-S-ST

UPRIGHT BAKERY REFRIGERATOR




Key Features



Lower running cost




Powerful cooling
performance



Self Closing Door



Removal door gaskets



Round Interior Corners




Large and clear display



Drainage-Free Design



Dimensions & Specifications



MODEL	HR-148MC-S-ST
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.75kVA (3.50A)
ELECTRIC CONSUMPTION	367W
TEMPERATURE CONTROL	-6 to 12°C
STORAGE CAPACITY	1250L
WEIGHT	Net: 142kg (Gross: Approx. 177kg)
OUTSIDE DIMENSIONS	1400mm(W)× 800mm(D)×2050(-2080)mm(H)
PACKAGE	Carton(Wooden Pallet): 1460mm(W)×900mm(D)×2075mm(H)
NUMBER OF SHELVES	8pcs
REFRIGERANT	R290
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI SINGAPORE PTE. LTD.

18 Boon Lay Way #01-102 Tradehub21, 609966

TEL 6225 2612 FAX 6225 3219

www.hoshizaki.com.sg

