



HOSHIZAKI

CERTIFICATION



HACCP International




ISO9001


FTL-108MA-SD LOW DRAWER UNDERCOUNTER FREEZER



Key Features



**Forced Evaporation
System**









**1/1 GN Compatible
Drawers**

(GN Trays are not included)*
*Max. Depth 100mm

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	FTL-108MA-SD
POWER SUPPLY	1 Phase 220 - 240V 50Hz Capacity: 0.95kVA(4.3A)
ELECTRIC CONSUMPTION	409W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -23 to -7° C
EFFECTIVE CAPACITY	85L
WEIGHT	Net: 76kg (Gross 81kg)
OUTSIDE DIMENSIONS	980mm(W) × 750mm(D) × 570 (560-590) mm(H)
PACKAGE	Carton 1045mm(W) × 830mm(D) × 560mm(H)
AMPERAGE	Rated: 3.0 A
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI MALAYSIA SDN. BHD.

16, JALAN TP5A, Prestij 16,
Taman Perindustrian Uep, 47620 Subang Jaya, Selangor
TEL +603-8023 5823 <https://hoshizaki.com.my/>

