



HOSHIZAKI

CERTIFICATION



HACCP International




ISO9001

FTL-146MA-SD LOW DRAWER UNDERCOUNTER FREEZER



Key Features



**Forced Evaporation
System**










**2/3 GN Compatible
Drawers**

(GN Trays are not included)*
*Max. Depth 100mm

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	FTL-146MA-SD
POWER SUPPLY	1 Phase 230V 50Hz Capacity: 0.95kVA(4.3A)
ELECTRIC CONSUMPTION	Heater: 439W Defrost: 330W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -23 to -7° C
EFFECTIVE CAPACITY	129L
WEIGHT	Net: 111kg (Gross 116kg)
OUTSIDE DIMENSIONS	1400mm(W) × 680mm(D) × 570 (560-590) mm(H)
PACKAGE	Carton 1465mm(W) × 680mm(D) × 560mm(H)
AMPERAGE	Rated: 3.0A
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI MALAYSIA SDN. BHD.

16, JALAN TP5A, Prestij 16,
Taman Perindustrian Uep, 47620 Subang Jaya, Selangor
TEL +603-8023 5823 <https://hoshizaki.com.my/>

