



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001

FTL-188MA-SD LOW DRAWER UNDERCOUNTER FREEZER



Key Features



**Forced Evaporation
System**




**1/1 GN Compatible
Drawers**

(GN Trays are not included)*
*Max. Depth 100mm

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	FTL-188MA-SD
POWER SUPPLY	1 Phase 220 - 240V 50Hz Capacity: 0.79kVA(3.6A)
ELECTRIC CONSUMPTION	453W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -23 to -7° C
EFFECTIVE CAPACITY	267L
WEIGHT	Net: 126kg (Gross 131kg)
OUTSIDE DIMENSIONS	1820mm(W) × 750mm(D) × 570 (560-590) mm(H)
PACKAGE	Carton 1865mm(W) × 830mm(D) × 560mm(H)
AMPERAGE	Rated: 2.4 A
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI (THAILAND) LIMITED

No. 99 CP Tower North Park building 9th Floor, Zone D1, Soi Ngamwongwan 47

Intersection 42, Thung Song Hong, Subdistrict, Lak Si District, Bangkok 10210

TEL +66 2 005 9980 FAX +66 2 516 2646 <https://hoshizaki.co.th/en/>

