



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001


RTL-188MA-SD LOW DRAWER UNDERCOUNTER REFRIGERATOR



Key Features



**Forced Evaporation
System**




**1/1 GN Compatible
Drawers**

(GN Trays are not included)*
*Max. Depth 100mm






Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



VIEW A (1/10)



MODEL	RTL-188MA-SD
POWER SUPPLY	1 Phase 220 - 240V 50Hz Capacity: 0.5kVA(2.27A)
ELECTRIC CONSUMPTION	257W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -6 to 12° C
EFFECTIVE CAPACITY	267L
WEIGHT	Net: 120kg (Gross 125kg)
OUTSIDE DIMENSIONS	1820mm(W) × 750mm(D) × 570 (560-590) mm(H)
PACKAGE	Carton 1865mm(W) × 830mm(D) × 560mm(H)
AMPERAGE	Rated: 1.9 A
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

PT. HOSHIZAKI INDONESIA

Kirana Boutique Office Kirana Avenue 2 Blok C2 No. 6 Jl. Raya
Boulevard No.1 Kelapa Gading, Jakarta Utara, DKI Jakarta, 14240
TEL +62-21-2937 5551/2 FAX +62 21 2937 5553
<https://hoshizaki.co.id/>

