



HOSHIZAKI

CERTIFICATION



HACCP International




ISO9001

HR-78MA-PLG

UPRIGHT LONG GLASS DOOR REFRIGERATOR




Key Features



Forced Evaporation System



LED Interior Lighting




Glass Door with Heater

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	HR-78MA-PLG
POWER SUPPLY	1 Phase 230V 60Hz Capacity: 0.74kVA (3.36A)
ELECTRIC CONSUMPTION	Heater: 463W, Defrost: 250W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -2 to 12° C
EFFECTIVE CAPACITY	569L
WEIGHT	Net: 108kg (Gross 128kg)
OUTSIDE DIMENSIONS	700mm(W)× 800mm(D)×2050(-2080)mm(H)
PACKAGE	Carton: (Wooden Pallet) 760mm(W)×900mm(D)×2075mm(H)
AMPERAGE	Rated: 3.1A
SHELF	4 pcs
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI PHILIPPINES CORPORATION

Unit No. GB-2, G/F Agustin 1 Bldg., # 28 F. Ortigas Center, Pasig City

TEL +632 8839 2861 <https://hoshizaki-sea.com/>

