



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001

RT-156MA-S-ML UNDERCOUNTER PILLAR-LESS REFRIGERATOR




Key Features



**Forced Evaporation
System**



**LED Interior
Lighting**










**Pillar-less
design**

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	RT-156MA-S-ML
POWER SUPPLY	1 Phase 230V 50Hz Capacity: 0.5kVA (2.5A)
ELECTRIC CONSUMPTION	Motor: 260W Heater: 189W Refrigeration: 245W Defrost: 165W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -6 to 12° C
EFFECTIVE CAPACITY	318L
WEIGHT	Net: 81kg (Gross: Approx. 86kg)
OUTSIDE DIMENSIONS	1500mm(W)× 600mm(D)×850(-880)mm(H)
PACKAGE	Carton: 1565mm(W)×680mm(D)×790mm(H)
AMPERAGE	Rated: 2.0A
SHELF	4 pcs
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI MALAYSIA SDN. BHD.

16, JALAN TP5A, Prestij 16,
Taman Perindustrian Uep, 47620 Subang Jaya, Selangor
TEL +603-8023 5823 <https://hoshizaki.com.my/>

