



ITEM	HOSHIZAKI UNDERCOUNTER FREEZER
MODEL	FTV-186A
△ POWER SUPPLY	SINGLE PHASE, 220-240V AC, 50HZ
RATED CURRENT	2.5 AMPS
△ RATED POWER	550 W (HEATER 370W)
HEAT REJECTION	1.083 kW
POWER CORD	10 AMPS / 3 METER
EFFECTIVE CAPACITY	386 L
OUTSIDE DIMENSIONS	1800MM(W)X600MM(D)X850(-870)MM(H)
INSIDE DIMENSIONS	1432MM(W) X 480MM(D) X 588MM(H)
EXTERIOR	SS 430 HAIRLINE NO 4 FINISH, GALVANIZED STEEL POWDER COATED (REAR/BOTTOM)
INTERIOR	SS 430 HAIRLINE NO 4 FINISH
INSULATION	POLYURETHANE FOAM (CFC FREE)
INSULATION FOAM BLOWING AGENT	CYCLOPENTANE
REFRIGERATION SYSTEM	FORCED AIR CIRCULATION
DEFROST SYSTEM	HEATER DEFROST (295 W)
△ COMPRESSOR	HERMETIC 650 W
CONDENSER	FORCED (WIRE ON TUBE)
EVAPORATOR	FORCED (FIN & TUBE)
REFRIGERANT/ CHARGE	R290 / 75 Gram
TEMP. CONTROL	ELECTRONIC ADJUSTABLE FROM -7°C TO -23°C
DEFROST CONTROL	BY TEMPERATURE CONTROLLER
ELECTRIC CIRCUIT PROTECTION	NON RESETTABLE FUSE (GLASS FUSE) 10 AMP
COMPRESSOR PROTECTION	MOTOR PROTECTOR
LEG	PLASTIC ADJUSTABLE 150 TO 170MM
SHELF	6 PCS
WEIGHT	NET: 124 KG (GROSS: APPROX 144 KG)
PACKAGE	CARTON (WOODEN PALLET) 1870MM (W) X 670MM (D) X 875MM(H)
ACCESSORIES	SHELF CLIPS
OPERATING CONDITIONS	AMBIENT TEMPERATURE : 5 - 43°C VOLTAGE RANGE RATED VOLTAGE ±6%
CABINET LAMP	LED STRIP TYPE 1310MM, 10W, DC24V
LAMP DRIVER	ELECTRONIC DRIVER 12W

*WE RESERVE THE RIGHT TO MAKE CHANGES IN SPECIFICATIONS AND DESIGN WITHOUT PRIOR NOTICE

1. INSTALL THE PRODUCT PROPERLY IN ACCORDANCE WITH THE INSTRUCTIONS ON LOCATION, ELECTRICAL CONNECTIONS STATED IN THE INSTRUCTION MANUAL PROVIDED.
ALLOW 10MM EXTRA SPACE AT THE INSTALLATION SITE TO MEET ANY INSTALLATION REQUIREMENTS (ADDITIONAL SPACING IS ALSO REQUIRED FOR PROPER AIR FLOW AND PIPE CONNECTIONS).
2. THE HEAT REJECTION IS BASED ON THE REACHED PULL DOWN TEMPERATURE AT AMBIENT TEMPERATURE OF 43°C AND POWER SUPPLY OF 230VAC 50HZ.
THE AMPERAGE AND ELECTRIC CONSUMPTION ARE BASED ON MEASUREMENT AT AMBIENT TEMPERATURE OF 43°C AND POWER SUPPLY OF 230VAC 50HZ.
3. TOLERANCE ON WEIGHT IS ±5 KG
4. PRODUCT CODE: KT12

HOSHIZAKI UNDERCOUNTER FREEZER FTV-186A

APPROVED	CHECKED	DESIGNED	DRAWN	SCALE	TRIGONOMETRY
NGOC SANG	NGOC SANG	BA HUY	BA HUY	1/20	
NGOC SANG	BA HUY	△	2026.01.30	DATE	DRAWING NO.
APPROVED	DESIGNED	SYMBOL	DATE	2025.12.25	D44239