EQ-4101
様式-26

HOSHIZAKI







ITEM	Hoshizaki Reach-in Refrigerator
MODEL	HR-128MC-S
POWER SUPPLY	1 Phase 220V ~ 240V 50Hz Capacity: 0.63kVA (2.90A)
AMPERAGE	Rated: 2.5A
ELECTRIC CONSUMPTION	MOTOR 283W(POWER FACTOR 85%) Heater 415W Refrigeration 429W Defrost 250W
HEAT REJECTION	1063W
POWER CORD	Plug with Earth Wire
EFFECTIVE CAPACITY	1043L
OUTSIDE DIMENSIONS	1200mm(W) x 800mm(D) x 2050(-2080)mm(H)
INSIDE DIMENSIONS	1096mm(W) x 646mm(D) x 1484mm(H)
EXTERIOR	Stainless Steel, Galvanized Steel(Top, Rear, Bottom)
INTERIOR	Stainless Steel, ABS Plastic(Door)
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Heater
COMPRESSOR	Hermetic
CONDENSER	Wire and Tube type, Air-cooled
EVAPORATOR	Fin and Tube type
REFRIGERANT	R290
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -6 to 12℃
DEFROST CONTROL	Microprocessor
ELECTRIC CIRCUIT PROTECTION	Earth Wire, Circuit Breaker
REFRIGERANT CIRCUIT PROTECTION	Motor Protector (Auto-reset)
LEG	Plastic Adjustable from 150 to 180mm
SHELF	8 pcs.
WEIGHT	132kg (Gross 161kg)
PACKAGE	Carton (Wooden Pallet) 1260mm(W) x 900mm(D) x 2075mm(H)
ACCESSORIES	Drain Hose x 1,Drain Pan x 1
OPERATING CONDITIONS	Ambient Temperature: 5 – 38℃ Voltage Range: Rated Voltage ±6%

*We reserve the right to make changes in specifications and design without prior notice.







1. Install the product properly in accordance with the instructions on location, water supply/ drain connections and electrical connections stated in the instruction and installation manuals provided.
   Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 35℃
3. Product Code: S175-V100 HVN
   S175-V200 HID
   S175-V300 HTH
   S175-V400 HMY

HOSHIZAKI REACH-IN REFRIGERATOR HR-128MC-S

APPROVED	CHECKED	DESIGNED	DRAWN	SCALE	
LIANG	LIANG	LIU	LIU	1/20	TRIGONOMETRY
LIANGK	LY	2025.1.12	DATE	DRAWING NO.	SYMBOL
APPROVED	DESIGNED	DATE	2025.06.05	D42539	1

000520
施行