



ITEM	Hoshizaki Undercounter Refrigerator
MODEL	RT-158MC-S
POWER SUPPLY	1 Phase 220-240V~ 50Hz Capacity: 0.41kVA (1.86A)
AMPERAGE	Rated 1.0A
ELECTRIC CONSUMPTION	Motor 151W(Power Factor 97%) Heater 214W Refrigeration 175W Defrost 190W
HEAT REJECTION	476W
POWER CORD	2.0m (UK Plug with Earth Wire)
EFFECTIVE CAPACITY	Net:291.5L/Gross:424L (Based on ISO 22041-2019)
ENERGY CONSUMPTION	1.80kWh/day (Based on ISO 22041-2019)
OUTSIDE DIMENSIONS	1500mm (W) x 750mm (D) x 850 (-880) mm (H)
INSIDE DIMENSIONS	1140mm (W) x 586mm (D) x 599mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom)
INTERIOR	ABS Plastic (Top & Bottom on Door)
INSULATION	Stainless Steel, ABS Plastic (Door)
INSULATION FOAM BLOWING AGENT	Polyurethane Foam
REFRIGERATION SYSTEM	Cyclopentane
DEFROST SYSTEM	Forced Air Circulation
COMPRESSOR	Glass Tube Heater
CONDENSER	Hermetic
EVAPORATOR	Wire and Tube type, Air-cooled
REFRIGERANT	R290
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from -6 to 12℃
DEFROST CONTROL	Microprocessor controlled
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
COMPRESSOR PROTECTION	Motor Protector
LEG	Plastic Adjustable 150 - 180mm
SHELF	4pcs.
WEIGHT	Net: 94kg (Gross: Approx. 106kg)
PACKAGE	Carton 1565mm (W) x 850mm (D) x 845mm (H)
ACCESSORIES	-
OPERATING CONDITIONS	Ambient Temperature: 5-38℃ Voltage Range: Rated Voltage±6%

We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pull-down temperature at ambient temperature of 35℃ and power supply of 230V 50Hz. The amperage and electric consumption are based on measurements at ambient temperature of 38℃ and power supply of 230V 50Hz.
3. The cabinet temperature range of -6 to 12℃ is guaranteed at ambient temperature of 30℃.
4. Product code: T436-V060

# HOSHIZAKI UNDERCOUNTER REFRIGERATOR RT-158MC-S

APPROVED LANG	CHECKED LANG	DESIGNED LANG	DRAWN LANG	SCALE	TRIGONOMETRY
2025.11.21	2025.11.21	2025.09.16		1/20	D45387
APPROVED/DESIGNED SYMBOL					SW80 1