



ITEM	Hoshizaki Thawing Cabinet
MODEL	HR-78MA-S-JD
POWER SUPPLY	1 Phase 220V-50Hz Capacity: 1.49kW (6.5A)
AMPERAGE	Rated: 2.1A Starting: 11.3A
ELECTRIC CONSUMPTION	MOTOR 225W(POWER FACTOR 53%) Heater 930W Refrigeration 326W Defrost 250W
HEAT REJECTION	677W
POWER CORD	2.5m
EFFECTIVE CAPACITY	525L
OUTSIDE DIMENSIONS	700mm(W)x800mm(D)x2050(-2080)mm(H)
INSIDE DIMENSIONS	596mm(W)x596mm(D)x1484mm(H)
EXTERIOR	Stainless Steel, Galvanized Steel(Top, Rear, Bottom)
INTERIOR	Stainless Steel, ABS Plastic
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Heater
COMPRESSOR	Hermetic
CONDENSER	Wire and Tube type, Air-cooled
EVAPORATOR	Fin and Tube type
REFRIGERANT	R134a
TEMPERATURE CONTROL	Refrigerator Microprocessor (Digital Temp. Indication) Adjustable from -6 to 12°C Thawing Microprocessor (Digital Temp. Indication) Adjustable from 2 to 20°C
DEFROST CONTROL	Microprocessor
ELECTRIC CIRCUIT PROTECTION	Earth Wire, Circuit Breaker
REFRIGERANT CIRCUIT PROTECTION	Motor Protector (Auto-reset)
LEG	Plastic, Adjustable from 150 to 180mm
SHELF	7 pcs.
WEIGHT	105kg (Gross 130kg)
PACKAGE	Carton (Wooden Pallet) 760mm(W)x900mm(D)x2075mm(H)
ACCESSORIES	Drain Hose x 1, Drain Pan x 1
OPERATING CONDITIONS	Ambient Temperature: 5 ~ 38°C Voltage Range: Rated Voltage ±6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided.
Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pull-down temperature at ambient temperature of 35°C

3. Product Code: R590-W102

HOSHIZAKI Thawing Cabinet HR-78MA-S-JD

APPROVED	CHECKED	DESIGNED	DRAWN	SCALE	1/20	TRIGONOMETRY
TUT	WZT	WANGAN	WANGAN			
REV	UNION	DATE	2025.10.10	DRAWING NO.	D43772	SHEET
APPROVED/DESIGNED	SHEET	DATE	2025.10.10			