






SRM-270AB -14-B-501SA

ICE MAKER





ICEMATE is committed to bringing highefficiency / energy-saving, and high quality ice-making product to people who have dreams and desire to create their own business with the best scientific technology and manufacturing technology.

KEY FEATURES

SAFETY AND HYGIENE ASSURED ICE MACHINE

AUTO-CLEANING

Timely maintenance of water system can extend life of equipment.

PURE ICE

Overflow self-cleaning function, ensuring ice hygiene

IoT



Slow melt Dilution


Slow Dilution

Powerful Ice Making




Energy & Water Saving, Quiet Operation







BIN TOP VIEW




RIGHT SIDE



BACK SIDE



FRONT SIDE



SPECIFICATIONS

Ice Dimensions (W x D x H)	29 x 14 x 22 mm
Outside Dimensions (W x D x H)	762 x 820 x 1671 (~1701) mm
Package Dimensions (W x D x H)	Ice Maker: Pallet+Carton: 850 x 710 x 750mm Storage Bin: 866 x 924 x 1138mm
Weight (Net / Gross)	Ice Maker: 59kg / 78kg Storage Bin: 47kg / 57kg
Amperage / Starting Amperage	4.96A/24A
Electrical Consumption	(AT32°C / WT21°C) 938.3W
Refrigerant Charge	R404A/620g
Ice Storage Capacity	Maximum 217kg
Ice Production per 24H	(AT10°C / WT10°C) Approx. 275 kg (AT21°C / WT15°C) Approx. 225kg (AT32°C / WT21°C) Approx. 183 kg

Water Consumption per 24H	(AT32°C/WT21°C) 0.19m³ (1.0L / kg lce)
Ice Production Freeze Cycle Time	(AT21°C/WT15°C) 16.5 min
Ice Production per Cycle	(AT21°C/WT15°C) Approx. 2.57kg / 320pcs

OPERATING CONDITIONS

Voltage Range	198 - 242 V
Ambient Temperature	5 - 38°C
Water Supply	5 - 32°C
Water Supply Pressure	0.07 - 0.55 Mpa (0.7 - 5.5 bar)
Supply Voltage	1/220 - 240V / 50Hz