

CERTIFICATION



HACCP International



ISO9001


ICE MATE



SRM-105A ICE MAKER

ICEMATE is committed to bringing high-efficiency / energy-saving, and high quality ice-making product to people who have dreams and desire to create their own business with the best scientific technology and manufacturing technology.

DICE




KEY FEATURES

SAFETY AND HYGIENE ASSURED ICE MACHINE



NSF Certified Material for Bin and Scoop



Detachable Parts for Easy Cleaning



Air Filter Prevent Dust from Entering



Stainless Steel

ENERGY & WATER SAVING, QUIET OPERATION




Energy & Water Saving, Quiet Operation

EASY MAINTENANCE




IoT







TOP SIDE




FRONT SIDE



RIGHT SIDE



BACK SIDE



SPECIFICATIONS

Ice Dimensions (W x D x H)	22 x 22 x 22 mm	Water Consumption per 24H	(AT32°C/WT21°C) 0.14m ³ (2.0L / kg Ice)
Outside Dimensions (W x D x H)	660 x 670 x 1200 mm	Ice Production Freeze Cycle Time	(AT21°C/WT15°C) 20 min
Package Dimensions (W x D x H)	Carton: 785 x 860 x 1250 mm	Ice Production per Cycle	(AT21°C/WT15°C) Approx. 1.17kg / 126 pcs
Weight (Net / Gross)	61 kg / 69 kg	OPERATING CONDITIONS	
Amperage / Starting Amperage	3.2A / 15.0A	Voltage Range	198 - 254 V
Electrical Consumption	(AT32°C / WT21°C) 480 W	Ambient Temperature	5 - 38°C
Refrigerant Charge	R404A / 290g	Water Supply	5 - 32°C
Ice Storage Capacity	Maximum 43.6kg	Water Supply Pressure	0.07 - 0.55 Mpa (0.7 - 5.5 bar)
Ice Production per 24H	(AT10°C / WT10°C) Approx. 100 kg (AT21°C / WT15°C) Approx. 90 kg (AT32°C / WT21°C) Approx. 70 kg	Supply Voltage	1/220 - 240V / 50Hz

