

## CERTIFICATION



HACCP International




ISO9001

# ICE MATE

by  HOSHIZAKI

## SRM-105A ICE MAKER

**DICE**




ICEMATE is committed to bringing high-efficiency / energy-saving, and high quality ice-making product to people who have dreams and desire to create their own business with the best scientific technology and manufacturing technology.

### KEY FEATURES

#### SAFETY AND HYGIENE ASSURED ICE MACHINE



NSF Certified Material for Bin and Scoop



Detachable Parts for Easy Cleaning



Air Filter Prevent Dust from Entering



Stainless Steel

#### ENERGY & WATER SAVING, QUIET OPERATION




Energy & Water Saving, Quiet Operation

#### EASY MAINTENANCE




IoT







TOP SIDE




FRONT SIDE



RIGHT SIDE



BACK SIDE



SPECIFICATIONS

Ice Dimensions (W x D x H)	22 x 22 x 22 mm
Outside Dimensions (W x D x H)	660 x 670 x 1200 mm
Package Dimensions (W x D x H)	Carton: 785 x 860 x 1250 mm
Weight (Net / Gross)	61 kg / 69 kg
Amperage / Starting Amperage	4.0A / 20.0A
Electrical Consumption	(AT32°C / WT21°C) 530 W
Refrigerant Charge	R404A / 320g
Ice Storage Capacity	Maximum 43.6kg
Ice Production per 24H	(AT10°C / WT10°C) Approx. 108 kg (AT21°C / WT15°C) Approx. 95 kg (AT32°C / WT21°C) Approx. 78 kg

Water Consumption per 24H	(AT32°C/WT21°C) 0.17m <sup>3</sup> (2.2L / kg Ice)
Ice Production Freeze Cycle Time	(AT21°C/WT15°C) 18 min
Ice Production per Cycle	(AT21°C/WT15°C) Approx. 1.28kg / 126 pcs

OPERATING CONDITIONS

Voltage Range	198 - 254 V
Ambient Temperature	5 - 38°C
Water Supply	5 - 32°C
Water Supply Pressure	0.07 - 0.55 Mpa (0.7 - 5.5 bar)
Supply Voltage	1/220 - 230V / 60Hz

