

CERTIFICATION



HACCP International




ISO9001

ICE MATE

by  HOSHIZAKI

SRM-125A ICE MAKER

DICE




ICEMATE is committed to bringing high-efficiency / energy-saving, and high quality ice-making product to people who have dreams and desire to create their own business with the best scientific technology and manufacturing technology.

KEY FEATURES

SAFETY AND HYGIENE ASSURED ICE MACHINE



NSF Certified Material for Bin and Scoop



Detachable Parts for Easy Cleaning



Air Filter Prevent Dust from Entering



Stainless Steel

ENERGY & WATER SAVING, QUIET OPERATION




Energy & Water Saving, Quiet Operation

EASY MAINTENANCE




IoT







TOP SIDE




FRONT SIDE



RIGHT SIDE



BACK SIDE



SPECIFICATIONS

| | |
|--------------------------------|---|
| Ice Dimensions (W x D x H) | 22 x 22 x 22 mm |
| Outside Dimensions (W x D x H) | 660 x 670 x 1200 mm |
| Package Dimensions (W x D x H) | Carton: 785 x 860 x 1250 mm |
| Weight (Net / Gross) | 64.5 kg / 72 kg |
| Amperage / Starting Amperage | 3.9A / 18.4A |
| Electrical Consumption | (AT32°C / WT21°C) 590 W |
| Refrigerant Charge | R404A / 350g |
| Ice Storage Capacity | Maximum 43.6kg |
| Ice Production per 24H | (AT10°C / WT10°C) Approx. 125 kg (AT21°C / WT15°C) Approx. 106 kg (AT32°C / WT21°C) Approx. 81 kg |

| | |
|----------------------------------|--|
| Water Consumption per 24H | (AT32°C/WT21°C) 0.17m ³ (2.1L / kg Ice) |
| Ice Production Freeze Cycle Time | (AT21°C/WT15°C) 15 min |
| Ice Production per Cycle | (AT21°C/WT15°C) Approx. 1.17kg / 126 pcs |

OPERATING CONDITIONS

| | |
|-----------------------|---------------------------------|
| Voltage Range | 198 - 254 V |
| Ambient Temperature | 5 - 38°C |
| Water Supply | 5 - 32°C |
| Water Supply Pressure | 0.07 - 0.55 Mpa (0.7 - 5.5 bar) |
| Supply Voltage | 1/220 - 240V / 50Hz |

