

Key Features












Our A-Fit cabinet combines functionality and outstanding energy performance to meet Japanese quality standards, with precise temperature control to ensure food-ingredient freshness at all times. With the R290 natural refrigerant and a door switch preventing the evaporator fan from running while the refrigerator is open, they not only perform efficiently but also support a greener tomorrow.


This model is compliant with NEA's Mandatory Energy Labelling Scheme (MELS) at 3 Tick.























| MODEL | FT-128MC-S |
|----------------------|---|
| POWER SUPPLY | 1 Phase 220V~240V 50Hz / Capacity: 0.63kVA (2.90A) |
| ELECTRIC CONSUMPTION | Motor: 194W / Heater: 230W / Refrigeration: 234W / Defrost: 190W |
| TEMPERATURE CONTROL | Microprocessor (Digital Temp. Indication) Adjustable from -25 to -7°C |
| EFFECTIVE CAPACITY | Total 260L |
| WEIGHT | Net: 78kg / Gross 90kg |
| OUTSIDE DIMENSIONS | 1200mm(W)×750mm(D)×850(-880)mm(H) |
| PACKAGE | Carton (Wooden Pallet) 1265mm(W)×8300mm(D)×790mm(H) |
| AMPERAGE | Rated 1.6A |
| SHELF | 4 pcs |
| OPERATING CONDITIONS | Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6% |

HOSHIZAKI SINGAPORE PTE LTD

18 Boon Lay Way #01-102 , Tradehub 21 S609966 Tel: +65 6225 2612 Website: www.hoshizaki.com.sg