



HOSHIZAKI

CERTIFICATION



HACCP International




ISO9001


FTL-148MA-PD LOW DRAWER UNDERCOUNTER FREEZER



Key Features



**Forced Evaporation
System**









**1/1 GN Compatible
Drawers**

(GN Trays are not included)*
*Max. Depth 100mm

Our A-fit cabinet combines functionality and excellent energy performance to meet Japan quality level with precise temperature control to ensure food ingredient freshness at all time.



Dimensions & Specifications



MODEL	FTL-148MA-PD
POWER SUPPLY	1 Phase 220 - 240V 60Hz
ELECTRIC CONSUMPTION	Heater: 439W Defrost: 330W
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -23 to -7° C
EFFECTIVE CAPACITY	176L
WEIGHT	Net: 111kg (Gross 116kg)
OUTSIDE DIMENSIONS	1400mm(W) × 750mm(D) × 570 (560-590) mm(H)
PACKAGE	Carton 1465mm(W) × 830mm(D) × 560mm(H)
AMPERAGE	Rated:
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI PHILIPPINES CORPORATION

Unit No. GB-2, G/F Agustín 1 Bldg., # 28 F. Ortigas Center, Pasig City, 1605

TEL +632 8839 2861 <https://hoshizaki-sea.com/>

