



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001



Compliant with
IEC60335-2-89 Standard

HR-148MC-S UPRIGHT REFRIGERATOR



Key Features



Lower running cost



Strong cooling power



LED lighting



Drainage-Free Design



Large and clear display



Rounded corner




Removal door gaskets




NATURAL
REFRIGERANTS



Dimensions & Specifications



MODEL	HR-148MC-S
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.75kVA (3.50A)
ELECTRIC CONSUMPTION	5.02kWh/day
TEMPERATURE CONTROL	-6 to 12°C
STORAGE CAPACITY	1243L
WEIGHT	Net: 148kg (Gross: Approx. 183kg)
OUTSIDE DIMENSIONS	1400mm(W)× 800mm(D)×2050(-2080)mm(H)
PACKAGE	Carton(Woden pallet): 1460mm(W)×900mm(D)×2075mm(H)
NUMBER OF SHELVES	8pcs
REFRIGERANT	R290
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI SINGAPORE PTE. LTD.

18 Boon Lay Way #01-102 Tradehub21, 609966

TEL 6225 2612 FAX 6225 3219

www.hoshizaki.com.sg

