



HOSHIZAKI

CERTIFICATION



HACCP International



ISO9001



Compliant with IEC60335-2-89 Standard


HRF-128MC-S UPRIGHT DUAL TEMP




Key Features



Lower running cost



Powerful cooling performance




Self Closing Door



Removal door gaskets



Food Guard Shelf



Round Interior Corners



Large and clear display




Drainage-Free Design



LED lighting



Dimensions & Specifications



MODEL	HRF-128MC-S
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 2.16kVA (5.10A)
ELECTRIC CONSUMPTION	11.43kWh/day
TEMPERATURE CONTROL	Refrigerator: -6 to 12°C, Freezer : -25 to -7°C
STORAGE CAPACITY	976L (Refrigerator: 488L, Freezer: 488L)
WEIGHT	Net: 166kg (Gross: Approx. 195kg)
OUTSIDE DIMENSIONS	1200mm(W)× 800mm(D)×2050(-2080)mm(H)
PACKAGE	Carton(Woden pallet): 1260mm(W)×900mm(D)×2075mm(H)
NUMBER OF SHELVES	8pcs
REFRIGERANT	R290
OPERATING CONDITIONS	Ambient Temperature: 5 - 38°C, Voltage Range: Rated Voltage ±6%



HOSHIZAKI

HOSHIZAKI MALAYSIA SDN. BHD.

No. 12, Jalan Penyajak U1/45B. Hicom-Glenmarie Industrial Park, 40150 Shah Alam, Selangor

TEL (+60) 3 5569 8023 <https://hoshizaki.com.my/>

